

# Thermal Black Soft Touch 35 Micron

- Bi-axially Oriented Polypropylene Film (BOPP)
- SOFT TOUCH finish
- Exclusive peach skin texture
- Solid black finish
- Outstanding surface adhesion for all types of coatings, inks, hot-melt and foils
- Low melt thermal adhesive

Ever versatile and useable; this extensive range of Bi-axially Oriented Polypropylene Films (BOPP) include Corona pre-treated / coated and print receptive grades neatly paired with user friendly low-melt thermally activated adhesive.

Used daily by our customers on a range of products including luxury packaging, brochures, catalogues, book covers and jackets, labels and posters.

## Specifications

BASE FILM	Polypropylene Film (BOPP)
SURFACE FINISH	Black/Velvet
AVAILABLE STOCK WIDTHS	315, 440, 510, 630, 710

Other widths available upon request

## Typical Properties

PROPERTY		UNIT	TEST METHOD	VALUE
THICKNESS		( µm )		35
YIELD		m <sup>2</sup> /kg In <sup>2</sup> /Lb	Internal Test Method	31.4 22 075
WETTING TENSION	B	Dynes/cm	ASTM D 2578	≥ 42
C.O.F FILM/FILM	B/B		ASTM D1894	0.50
APPLICATION TEMPERATURE	A	°C °F	Internal Test Method	105 – 120 220 – 250
LAMINATION STRENGTH	A	N25.4/mm Lb/In	Internal Test method	≥ 7.5 ≥ 1.68
GLOSS	B	%	ASTM D 2457 45°	1

A: Adhesive Side B: Black Soft Touch Side

The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



01844 208308 info@gifproducts.co.uk www.gifproducts.co.uk