

Wet Sandy Gritty Matt 38 Micron

- Bi-axially Oriented Polypropylene Film (BOPP)
- Sandy gritty matt textured finish
- Good anti-scuff properties
- Hard wearing surface
- Outstanding surface adhesion for all types of coatings, inks, hot-melt & foils
- Compatible with our wet acrylic adhesive & hardener

Ever versatile and useable; this extensive range of Bi-axially Oriented Polypropylene Films (BOPP) include Corona pre-treated / coated and print receptive grades which can be used in conjunction with our GIF water based acrylic adhesive

Used daily by our customers on a range of products including luxury packaging, brochures, catalogues, book covers and jackets, labels and posters.

Specifications

BASE FILM	Polypropylene Film (BOPP)
SURFACE FINISH	GrittyMatt
AVAILABLE STOCK WIDTHS	440, 510, 630, 710

Other widths available upon request

Typical Properties

PROPERTY		UNIT	TEST METHOD	VALUE
THICKNESS		(µm)		38
YIELD		m ² /kg	Internal Test Method	53.76 37 801
WETTING TENSION	B	Dynes/cm	ASTM D 2578	≥ 38
C.O.F FILM/FILM	B/B		ASTM D1894	0.5
GLOSS	B	%	ASTM D 2457 45°	12

A: Inside B: Gritty Matt Side

The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



01844 208308 info@gifproducts.co.uk www.gifproducts.co.uk