BioRenew 30 Anti-Scratch Matt

Thermal BOPP Lamination Film

Anti-scratch matt BOPP film for thermal lamination. 30% renewable feedstock from used vegetable oils, attributed through certified mass balance.

Key features

- Enhanced scratch and scuff resistance
- 30% renewable feedstock (mass balance)
- Extra matt finish
- Recommended for dark printed designs
- ISCC PLUS certified product

Finishing compatibility

- Spot UV and hot foil stamping[1]
- Hot-melt gluing[1]
- Surface printing with most UV inks

Specifications

BASE FILM	Biaxially oriented polypropylene (BOPP)
SURFACE FINISH	Transparent extra matt, scratch-resistant

Typical properties

PROPERTY	THERMAL	UNIT	TEST METHOD
Thickness	30	µm	–
Yield	37.04	m²/kg	Internal method
Gloss[2]	5	%	Internal method
Surface tension	40	mN/m	ASTM D2578
Coefficient of friction	0.35	–	Internal method
Application temperature	110–120	°C	Internal method
Lamination strength	≥7.5	N/25.4 mm	Internal method

[1] Follow current handling guidance and confirm by trials. [2] Measured on 300 g/m² black-printed coated board under the supplier's stated test conditions.

30% renewable feedstock attributed through ISCC PLUS certified mass balance. Typical values are indicative. Confirm suitability and settings through lamination and finishing trials. Sustainability declarations available on request.

GIF PRODUCTS

01844 208308 info@gifproducts.co.uk www.gifproducts.co.uk

Graphic Image Films Ltd · Unit 5, Ridge Way · Crendon Industrial Park · Long Crendon · Buckinghamshire